

PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 1

Compilation date: 19/05/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PRIVATE LABEL STAINLESS STEEL CLEANER

Product code: PLB 1007 SPD1341

Pack Size: 12 x 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: FOR PROFESSIONAL AND INDUSTRIAL USE ONLY. Aerosol solvent cleaner.

1.3. Details of the supplier of the safety data sheet

Company name: STAPLES CHEMICALS

NEVILLE HOUSE BEAUMONT RD BANBURY OXON OX16 1RB

Tel: 01295 251721

Email: sales@cleenol.co.uk

Emergency Telephone: Poisons Information Specialist

National Poisons Information Service

Birmingham B18 7QH Tel: 0121 507 5122

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; -: R53; -: R66

Classification under CLP: Flam. Aerosol 1: H222; Aquatic Chronic 4: H413; -: EUH066; -: H229

Most important adverse effects: Extremely flammable. May cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H413: May cause long lasting harmful effects to aquatic life.

Signal words: Danger

Hazard pictograms: GHS02: Flame



PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 2

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P102: Keep out of reach of children.

P260: Do not breathe vapours.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Label elements under CHIP:

Hazard symbols: Extremely flammable.



Risk phrases: R12: Extremely flammable.

R53: May cause long-term adverse effects in the aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S37/39: Wear suitable gloves and eye / face protection.

S51: Use only in well-ventilated areas.

Precautionary phrases: Pressurised container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources

of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 3

Hazardous ingredients:

HYDROCARBONS, C11-12, ISOALKANES, <2% AROMATICS, <0.1% BENZENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
918-167-1	64741-65-7	-: R53; Xn: R65; -: R66	Acute Tox. 4: H302; Aquatic Chronic 4: H413; -: EUH066	50-70%
PROPANE				
200-827-9	74-98-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%

BUTANE

203-448-7	106-97-8	F+: R12	Flam. Gas 1: H220; Press. Gas: H280	10-30%
		Substance with a Community		
		workplace exposure limit.		

Non-classified ingredients:

WHITE MINERAL OIL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
232-455-8	8042-47-5	-	-	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately.

Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to

fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back. Aerosol cans may explode during a fire, giving a high speed projectile.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Cover leaking can until the discharge has stopped, before attempting cleanup operations. Spillage will create slippery surface.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 5

8.1. Control parameters

Hazardous ingredients:

HYDROCARBONS, C11-12, ISOALKANES, <2% AROMATICS, <0.1% BENZENE

Workplace exposure limits:

Respirable dust

State	8 hour TW A	15 min. STEL	8 hour TW A	15 min. STEL		
UK	1000mg/m3	n/a	-	-		
PROPANE						
UK	1800 mg/m3	7200 mg/m3	-	-		
BUTANE						
UK	1450 mg/m3	1810 mg/m3	-	_		

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Perceptible odour

Evaporation rate: Slow **Solubility in water:** Insoluble

Viscosity: Non-viscous

Boiling point/range°C: Not applicable. Melting point/range°C: Not applicable.

Flammability limits %: lower: 0.8 upper: 9.0

Flash point°C: -40 Autoflammability°C: >230

Vapour pressure: Not applicable. Relative density: Not applicable.

pH: Not applicable. VOC g/I: Not applicable.

9.2. Other information

Other information: No data available.

PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 6

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-12, ISOALKANES, <2% AROMATICS, <0.1% BENZENE

ORL	RAT	LD50	>5000	ma/Ka
OIL	11/41	LDJU	/3000	IIIq/IXq

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

${\bf HYDROCARBONS,\,C11\text{-}12,\,ISOALKANES,\,<2\%\,\,AROMATICS,\,<0.1\%\,BENZENE}$

TROUT	96H LC50	>1000 mg/L	
111001	9011 LC30	>1000 mg/L	

PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 7

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Insoluble in water. Floats on water. Vapour is heavier than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Recycling/reclamation of metals and metal compounds.

Disposal of packaging: Dispose of as normal industrial waste. Empty cans must not be burned because of

explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

PRIVATE LABEL STAINLESS STEEL CLEANER

Page: 8

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

IMPORTANT NOTE:

Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the

formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels

in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H302: Harmful if swallowed.

H413: May cause long lasting harmful effects to aquatic life.

R12: Extremely flammable.

R53: May cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.